


Technical Data Sheet

化学名称/Name			
中文化学名	高岭土	分子式 Molecular Formula	
English name	Kaolin	H2Al2O8Si2.H2O	
CAS.No	1332-58-7	分子量 Molecular weight	
Substance Type	Calcined kaolin	258. 16	

具体指标/Details	
项目/Item	典型值/Typical value
外观 Appearance	白色粉末 White powder
白度 Brightness(R457)%	93
粒径(-2 微米)% Particle Size(-2um)%	80±2
湿筛残留物(+325 目)% Wet Screen Residue, +325 Mesh,%	0.01
吸油值, 克/100 克 Oil Absorption, g/100g	58±5
游离水分% Free Moisture, %	0.5
pH 值 pH Value	6~8

应用/Application
对甲苯磺酸正丙酯常用作有机合成的原料，可用于酮或醇的甲磺化反应、酯的磺酸化反应等 Calcined kaolin, it used with superior kaolinite material, produced with the processes of de-ironing, fine grinding and specially controlled calcination. With its high reactivity property, it can absorb a great deal of fee electron among the rubber, PVC and other additives, effectively improve the insulation property of the cable.

运输/Transportation
产品在运输时应防火、防热、防雨淋、防受潮 Products should be protected from fire, heat, rain and moisture during transportation.

包装/Packing
塑料编织袋 25 公斤，超大袋 500 公斤。 25 kgs plastic woven bag,500 kgs jumbo bag.